Alpha Resources, Inc. Certificate Of Analysis

AR-2871

ULTRA LOW #2 DIESEL OIL STANDARD

LOT # 871108

LID # 871108

WEIGHT PERCENT SULFUR = 0.0100 STANDARD DEVIATION = 0.0005

The certified mean values were statistically derived from the values reported to Alpha Resources through Round Robin.

Methods: ASTM D 2622 ASTM D 4294 ASTM D 5453-93

This Certified Reference Material is traceable to N.I.S.T. 1616a & 1617a.

NOTES:

The above value represents the mean from the data, as reported by Alpha Resources' round robin program.

Before use, the contents of the bottle should be mixed though vigorous shaking. The contents should not be exposed to air for a lengthy period of time.

Normal ASTM procedures should be employed when using this standard. This includes using the reproducibility and repeatability factors. Use the reproducibility factor when establishing the first set of data, and then establish an internal repeatability factor as your guideline.

The material used in production of this standard was sampled in accordance with ARI 031. The above values relate only to the material used to produce this standard.

The overall direction and coordination of the analytical measurements leading to certification were performed by J.R. Shingledecker at Alpha Resources.

Remedies for any claimed defect in this product will be limited to product replacement or refund of the purchase price. In no event shall Alpha Resources be liable for incidental or consequential damages.

This is a Certified Reference Material (CRM), and is traceable to the above-mentioned standards. For good laboratory practice it is recommended that all standards be verified prior to use.

EXPIRATION DATE
THIS CRM IS VALID FOR TWO YEARS FROM THE DATE OF PURCHASE WHICH APPEARS ON THE BOTTLE

J.R. Shingledecher