

Alpha Resources, Inc.

Certificate Of Analysis

Engine oils

	LOT	% ASH	% Zn	% Ca	% Mg	% P	% S	Base No.	Viscosity
AR6301	AA	0.05	<0.001	<0.001	<0.001	<0.001	0.29	2.42	12.25/119.20
AR6302	EO	0.22	0.122	0.0005	0.0005	0.103	0.22	2.83	12.56/124.87
AR6303	100	0.83	0.101	0.009	0.105	0.084	0.40	5.42	11.44/102.70
AR6304	LDO	0.81	0.119	0.058	0.087	0.095	0.56	6.27	12.81/73.51
AR6305	300	0.78	0.155	0.168	0.052	0.126	0.57	7.07	11.52/98.74

Base Number is ASTM D 2896

Viscosity is Centistokes at 100 degrees C/40 degrees C.

Notes:

Normal ASTM procedures should be employed when using this standard. This includes using the *reproducibility* and *repeatability* factors. Use the reproducibility factor when establishing the first set of data, and then establish an internal repeatability factor as your guideline.

The statistical analysis and overall coordination leading to certification was performed by D.M. Reasons at Alpha Resources.

Remedies for any claimed defect in this product will be limited to product replacement or refund of the purchase price. In no event shall Alpha Resources be liable for incidental or consequential damages.

EXPIRATION DATE

THIS CRM IS VALID FOR TWO YEARS FROM THE DATE OF PURCHASE WHICH APPEARS ON THE BOTTLE

