

Alpha Resources, Inc.

Certificate Of Analysis

KEROSENE STANDARD

AR-2841
LOT# 841103
LID # 841103

WEIGHT PERCENT SULFUR = 0.0125
STANDARD DEVIATION= 0.0015

METHODS:
ASTM D-2622
ASTM D-4294
ASTM D-5453-93

NIST standard employed were SRM 1616a.

NOTES:

Before use, the contents of the bottle should be mixed through vigorous shaking. The contents should not be exposed to air for a lengthy period of time.

Normal ASTM procedures should be employed when using this standard. This includes using the reproducibility and repeatability factors. Use the reproducibility factor when establishing the first set of data, and then establish an internal repeatability factor as your guideline.

The material used in production of this standard was sampled in accordance with ARI 031. The above values relate only to the material used to produce this standard.

The overall direction and coordination of the analytical measurements leading to certification were performed by J.R. Shingledecker at Alpha Resources.

Remedies for any claimed defect in this product will be limited to product replacement or refund of the purchase price. In no event shall Alpha Resources be liable for incidental or consequential damages.

This is a Certified Reference Material (CRM), and is traceable to the above-mentioned standards. For good laboratory practice it is recommended that all standards be verified prior to use.

EXPIRATION DATE
THIS CRM IS VALID FOR TWO YEARS FROM THE DATE OF OPENING

J.R. Shingledecker

Alpha Resources, Inc. Certificate Of Analysis

