



Certificate of Analysis

AR-2773

ULTIMATE COAL CRM

LOT # 731123 LID # 731123

DRIED BASIS VALUES

Table with columns for Proximate Analysis, n, k, ASTM, Ultimate Analysis, n, k, ASTM. Rows include % Ash, % Volatile Matter, % Fixed Carbon, % Sulfur, and Btu/lb.

Table with columns for Mineral Analysis, n, k, ASTM, Sulfur Forms, n, k, ASTM, and Ash Fusion Temperature. Rows include % Silica, % Alumina, % Titania, % Ferric Oxide, % Calcium Oxide, % Magnesium Oxide, % Potassium Oxide, % Sodium Oxide, % Sulfur Trioxide, % Phosphorus Pentoxide, % Strontium Oxide, % Barium Oxide, % Manganese Oxide, % Pyritic, % Organic, % Sulfate, and various Ash Fusion Temperature parameters.

REFERENCES USED: Sulfur - NIST SRM 2682c, 1632d, NCS FC28006j, BTU - NIST 39j (Benzoic Acid); Mineral Analysis - NIST 1635a, 1634a; Chlorine - SRM 1635a, 1632d; Fluorine - SRM 1635a, 1632d. () Indicates reference or information only value.

The intended use of this standard is for the verification of various tests by the above-mentioned methods. Typical sample size for analytical testing and minimum size is subject to the test method and instrumentation used. The uncertainty values represent the expanded uncertainty obtained through analytical testing by the mentioned ASTM methods utilizing ANOVA, ISO Guide 35, and the Guide to Uncertainty Measurement.

The material used in production of this standard was identified in accordance with ARI-LAB-603. The samples for round-robin testing were selected in accordance with ARI-LAB-625. The above values relate only to the material used to produce this standard.

This is a Certified Reference Material (CRM) and is traceable to the above-mentioned references. For good laboratory practice it is recommended that all standards be verified as fit for purpose prior to use.

EXPIRATION DATE
THIS CRM IS VALID FOR TWO YEARS FROM THE DATE OF OPENING
CERTIFIED January 24, 2024. Kent Dyer - Chief Chemist