

Steel Pin Certified Reference Material

Product No: AR656**Lot No: 240219**

Material and Intended Use

AR656 is a steel pin certified reference material (CRM). The intended use of this CRM is for the verification and calibration of inert gas fusion and other appropriate analysis methods for the determination of oxygen and nitrogen. This CRM can also be used to validate value assignment of in-house reference materials. A unit consists of one bottle containing 50 g of reference material in nominal 0.5 g pins. All reference materials should be verified as fit for purpose prior to use.

Instructions for Use

This product requires no preparation prior to use. The minimum sample size for analysis is dependent upon the test method and instrumentation used. It is recommended that no less than 1 pin of CRM material be used for destructive test methods. Bottles of pins should be kept sealed tight and stored in a cool, dry location. Property values are valid for 20 years from the initial date of certification if handling and storage instructions are followed. However, values are rendered null and void if the CRM is in any way modified or damaged.

Reported Values

Property values for a chemical element indicate the amount of each element present in the overall material matrix and are metrologically traceable to the International System of Units (SI) derived unit of mass fraction expressed as a percent (%). Certified values are reported as the mean property value with an expanded uncertainty ($U_{95\%}$). The true value of the measurand is believed to lie within the expanded uncertainty coverage interval with 95% confidence. Expanded uncertainty is calculated by application of a coverage factor (k) to the combined standard uncertainty (u_c). For laboratory uncertainty budgets, the combined standard uncertainty can be calculated as $u_c = U_{95\%}/k$, where k is approximately equal to 2. The estimation of combined standard uncertainty (u_c) includes contributions from material homogeneity, primary calibrants, characterization, and other factors. Sampling and calculation of reported values for each measurand are performed using practices consistent with ISO 17034:2016 and ISO 33405:2024. Certified values are accredited under Alpha Resources, LLC ISO/IEC 17025 and ISO 17034 certificates issued by ANSI National Accreditation Board (ANAB), AT-1200 and AR1920.

Table 1. Certified values for AR656, Lot 240219.

Element	Certified Value	$U_{95\%}$	Method & Detection	n
% Oxygen	0.0030	0.0009	Inert Gas Fusion/IR	60
% Nitrogen	0.0249	0.0025	Inert Gas Fusion/TC	60

Certified values were validated using the following primary reference standards:

NCS	NS 11096, NS 11094
BAM	027-1, 026-2
JSS	611-11, 604-10
AR	656-618A

Homogeneity

This product was manufactured from a single heat lot of bulk material. Samples were randomly selected using practices consistent with ISO 33405:2024. Homogeneity was evaluated by replicate analysis. Within- and between-sample variance was evaluated using Analysis of Variance (ANOVA).

Methods and References

ARI-LAB-622 – Alpha Resources Method, Oxygen/Nitrogen Analysis

ASTM E1019 – Standard Test Methods for Determination of Carbon, Sulfur, Nitrogen, and Oxygen in Steel, Iron, Nickel, and Cobalt Alloys by Combustion and Inert Gas Fusion Techniques

ISO/IEC 17025:2017 – General requirements for the competence of testing and calibration laboratories

ISO 17034:2016 – General requirements for the competence of reference material producers

ISO 33401:2024 – Reference materials – Contents of certificates, labels, and accompanying documentation

ISO 33405:2024 – Reference materials – Approaches for characterization and assessment of homogeneity and stability

ISO Guide 30:2015 – Terms and definitions used in connection with reference materials

**Dustin Jenkins, Ph.D.****Global Technical Director****Certification Date:** January 06, 2025**Updated:** September 10, 2025

This certificate cannot be reproduced except in full. Remedies for any claimed defect in this product will be limited to product replacement or refund of the purchase price. In no event shall Alpha Resources, LLC be liable for incidental or consequential damages. Produced in accordance with ISO 17025 and ISO 17034.